

URIT

Fast speed simplify your lab work

URIT-330

Urine Analyzer



Global Diagnostics Supplier

URIT-330

Urine Analyzer

Specifications

Parameters: Leukocyte, Ketone, Nitrite, Urobilinogen, Bilirubin, Protein, Glucose, Specific Gravity, Blood, pH, Ascorbic Acid, Microalbumin, Creatinine, Calcium

Measurement Principle: Dual wavelength reflectance photometry

Measuring Wavelength: 4 LED Wavelength (470nm, 550nm, 620nm, 720nm)

Reaction time: 60 seconds

Throughput: 510 samples /hour

Display: LCD display

Memory Capacity: 9999 results

Strip: URIT 10G/11G urine reagent strips (13G, 14G, 11F, 12F optional)

Interface: Serial port(RS232), parallel port (For external printer), PS/2(For barcode reader), USB Port(For data out put)

Work condition: Environmental Temperature: 15-30°C,
RH: 20%~80%, Lumination: =2000 lx

Power supply: 100~240V AC, 50/60Hz, 35W~50W.

Dimension: 390mm x 340mm x 290mm

Weight: 6.1kg



URIT URINE CONTROL

Features

- ▣ Friendly operation with four shortcut keys
- ▣ Easy to installation and maintenance
- ▣ Fully automatic operation for ready-to-test
- ▣ Internal calibration for sensitivity of strips
- ▣ Interface to host PC/LIS, Barcode reader optional
- ▣ URIT UQ Urinalysis Control



URIT 10G、11G、14G urine reagent strip

Complete urine analysis with ascorbic acid

URIT MEDICAL ELECTRONIC (GROUP) CO., LTD.

Head Office

Add.: No.4 East Alley, Jiu Hua Road, Guilin,
Guangxi 541001, P.R. China

Tel: +86-773-2288586 Fax: +86-773-2288560

E-mail: export@uritest.com service@uritest.com

Shenzhen Office

Add.: Room E.J, 24th Floor, New Baohui Building, Nanshan Road,
Nanshan District, Shenzhen, P.R. China

Tel: +86-755-26050853 Fax: +86-755-86036150

Http://www.urit.com



ISO9001
ISO13485